

STROOMAGGREGAAT GE 14000 YS/GS EAS

- Yanmar watergekoelde dieselmotor
- EP6 motorbeveiliging
- Driefase synchrone generator
- Uitgangen : 1 x 400V 32A 3P+N+T CEE
- 1 x 400V 16A 3P+N+T CEE -1 x 230V 32A 2P+T CEE
- 1 x 230V 16A 2P+T SCHUKO
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Centraal hijsoog
- Onderstel (optie)
- Compacte bouw, stil en robuust
- Betaalbare topkwaliteit



Standaard uitvoering											
	Diesel engine	Water cooling	Battery 12V	Fuel level gauge	Engine protection	Electric Starter	low press. shut down	high water shut down	over speed shut down	low fuel shut down	battery charge alarm
						Rpm-meter	Hours-meter	Battery Voltmeter	Voltmeter	Frequency-meter	Ammeter
Opties											
	Synchronous alternator	Compound	Sockets 3~	Sockets 1~	ELCB-GFI	Circuit Breaker	Voltmeter phase selector	Emergency stop button	Ready for EAS/TCM	Local/remote start selector	Central lifting eye
	400V plug 230V plug - Earthing kit				- Remote control - Tank locking cap - Automatic transfer unit (AMF) EAS 28-805				- Site tow CTL300 - Road trolley CTV4		

Technische gegevens

GE 14000 YS/GS EAS

A.C. GENERATOR - 50 Hz	Three-phase synchronous alternator, self-excited, self-regulated
* Stand-by three-phase power * P.R.P. three-phase power * P.R.P. single-phase power Cos φ Insulation class * Output powers according to ISO 8528-1	14 kVA (11.2 kW) / 400 V / 20.2 A 13 kVA (10.4 kW) / 400 V / 18.8 A 5 kVA / 230 V / 21.7 A 0.8 H
MOTOR	4-stroke diesel, water cooled, indirect injection
Model * Stand-By net power * P.R.P. net power Cylinders/ Displacement Speed Fuel consumption (75% of P.R.P.) * Powers according to ISO 3046-1	Yanmar 3 TNV 70 13.3 kW (18.1 HP) 12.1 kW (16.5 HP) 3 / 854 cm ³ 3000 rpm 3.3 l/h
ALGEMENE SPECIFICATIES	
Tank capacity Running time (75% of P.R.P.) IP protection degree *Dimensions LxWxh (mm) *Dry weight **Measured acoustic power LwA (pressure LpA) **Guaranteed acoustic power LwA (pressure LpA) * Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC	30 l 9 h IP 23 1460x700x920 mm 390 kg 95 dB(A) (70 dB(A) @ 7m) 96 dB(A) (71 dB(A) @ 7m)